


TV9-304UW




Specifications

- Picture Tube :** 9", 90° Deflection, Aluminized Screen*
- Transistor :** 29 (5 Silicon—including 2 Epitaxial 24 Germanium)
- Diode :** 16 and 4 Selenium Rectifier
- Channel Coverage :** A2...A13 VHF and A14...A83 UHF
- Maximum Sensitivity :** 10 μ V/10 Vpp at Picture Tube Cathode
- IF Circuit :** 4 Stages with 5 stagger tuned elements
Video IF 26.75 Mc, Sound IF 22.25 Mc,
Bandwidth 3.0 Mc/—3 dB, IF delivered from UHF Tuner 74 M
- Resolution :** Vertical 400 lines, Horizontal 300 lines
- Sound System :** 4.5 Mc Intercarrier System
Power Output Stage OTL System 320 mW
Speaker 2-3/4" \times 4" Oval Type, 40 Ω Voice Coil
- Automatic Control :** Pulse Operated AGC, Diode AFC
- Power Requirement :** AC 117 Volts, 50 or 60 c/s, DC 12 V Battery (3.5 AH)
- Power Consumption :** AC 17.5 W, DC 12.4 W
- Dimensions :** 9-5/8" \times 8-5/8" \times 7-3/8"
- Weight :** 11 lbs. 11 ozs.


SONY®
SERVICING GUIDE

CONTENTS


	Page
Specifications for SONY Transistor TV 9-304UW.....	1
THE SONY TRANSISTOR TV 9-304UW	4
GENERAL	4
THE TUNER	6
SIGNAL CIRCUIT BOARD SECTION	9
DEFLECTION CIRCUIT BOARD AND HIGH-VOLTAGE SECTIONS	13
POWER SUPPLY SECTION.....	15
METHOD OF DISASSEMBLING THE SET	15
To Remove the Back cover of the Cabinet	15
To Remove the Front Control Panel	15
To Remove the Tuner Block	16
To Remove the Potentiometers	17
To Check and To Remove the Signal Circuit Board	17
To Check and To Remove the Deflection Circuit Board	18
To Remove the Chassis from the Cabinet.....	18
To Remove the High Voltage Block	19
To Remove the Telescopic Antenna	20
To Remove the Picture Tube.....	20
TROUBLE SHOOTING	22
RASTER	22
VIDEO OUTPUT AND SYNCHRONIZATION	24
SOUND	25
Mounting Circuit Board	26
Voltage Distribution Chart	30
Wave Forms	31
Schematic Diagram	33
Parts List.....	35



(Fig. 1)



(Fig. 2)



(Fig. 3)

The SONY Transistor TV 9-304UW

General

The SONY Transistor TV 9-304UW is a 9 inch TV by which both VHF and UHF bands can be received without using an external UHF Converter.

The design was made to meet the following requirements.

- 1) To be not larger in size nor heavier in weight as compared to the Model 9-304W which is the VHF model.
- 2) To have the lowest power consumption of any mass produced 9 inch VHF/UHF TV set.
- 3) To operate perfectly as a completely portable TV set under all conditions.
- 4) To provide facilities for easy servicing.

To fulfil these requirements, many developments were made on the components and the circuit arrangements as explained below.

1. Picture Tube CT468

The resolution of the picture depends greatly upon the construction of the picture tube, and the power consumption of the TV set is much influenced by the construction of the electron gun in the tube. Therefore, the key point of success in making a superior TV set is the improvement of the picture tube. The CT468 picture tube was specially developed for the SONY Transistor TV 9-304UW and has the following features.

a) Resolution

Horizontal 28 lines per cm. (300 lines for full picture)
Vertical 45 lines per cm. (400 lines for full picture)

b) Deflection Power

90 degree deflection and a neck diameter of 20 mm (3/4") result in lower deflection power although the anode voltage is as high as 9 KV. This gives a brightness of 500 lux.


c) The power required for the heater is less than 1 watt.

d) The overall length of the tube is 195 mm. (7-11/16").

e) The cut-off voltage at the grid is made very low by introducing techniques developed in transistor manufacturing into the assembly of the electron gun. Consequently, satisfactory contrast is obtained at low video signal output.

Specifications of Picture Tube CT468

Type :	Rectangular Frame	Diagonal Dimension :	228 mm. (9")
Neck Diameter :	20 mm. (3/4")	Full Length :	195 mm. (7-11/16")
Deflection :	Electromagnetic	Focusing :	Electrostatic Automatic
Deflection Angle :	90 degree	Ion Trap :	Unnecessary
Heater Voltage :	12.0 V, 70 mA	Anode Voltage :	9 KV
Anode Current :	150 μ A	2nd Grid Voltage :	400 V
Focusing Voltage :	0—200 V	1st Grid Cut-off Voltage :	Approx. —25 V



(Fig. 4)

Picture Tube



(Fig. 5)

2. The Tuner

The Tuner Block was the key point of success in remaining the size of the set exactly the same as that of the 9-304W, the VHF single band model. The Tuner Block consists of VHF and UHF Tuners of which the former was specially designed to make the size as small as possible.

The UHF Tuner is of newly developed one which includes tuning circuit of particular type and Esaki Diode for the mixer.

Band setting is done by simply turning the Channel Selector Knob for the VHF Tuner to UHF position and by doing thus, the Fine Tuning Knob for the VHF Tuner automatically changes its function to serve as a Tuning Knob for the UHF Tuner.


3. Automatic Gain Control Circuit

The AGC system is of pulse type. With the use of this circuit the SONY Transistor TV 9-304UW will maintain synchronization even in moving car where the signal strength varies suddenly and almost continuously and even in the presence of strong engine noise radiation.


4 Provision for Easy Servicing

Small size usually means difficult servicing. The SONY Transistor TV 9-304UW is divided into five sections for easy service. The sections are: Tuner, Signal Circuit Board, Deflection Circuit Board, High Voltage Block and Power Supply. The Signal Circuit Board and the Deflection Circuit Board are of the Plug-in type so that either of these boards may be removed as a unit and replaced with a new one for easy and rapid repairing.


Level Diagram for Video



(Fig. 6)



(Fig. 7)



(Fig. 8)

The Tuner


The Tuner Block consists of VHF Tuner and UHF Tuner. As shown in the block diagram, the Input Signal comes directly into the RF amplifier stage of the VHF Tuner in VHF reception while in UHF reception, the Input Signal is fed to the RF amplifier stage of the VHF Tuner after it is converted into VHF signal of which center frequency is 74 Mc through the UHF Tuner.

1. VHF Tuner


The VHF Tuner uses three PNP Mesa Type Germanium Transistors (2SA161), one is used in the RF Amplifier,

one is the Mixer and one in the Local Oscillator. A Disc Type Turret is used for mounting all the coils and contacts for Channel Selection. Special Contact Points have been designed for easy and positive channel selection. The transistors and other circuit parts are mounted directly above the Channel Switch and are enclosed within the Tuner Shield. RF coils for each channel are connected in series but the Oscillator Coil for each channel can be adjusted independently. The AGC characteristics of the set is excellent as the AGC action is extended to the IF Amplifier and to the RF Amplifier Stage in the VHF Tuner. The Set with the built-in Telescopic Antenna extended to its full length can be operated at a field strength of as much as 100mV/m without overloading the circuit.


Block Diagram for the Tuner Block



(Fig. 9)



(Fig. 10)




(Fig. 11)

a. RF Amplifier

The Antenna Impedance is 75Ω . For correct impedance matching between the Antenna and the Transistor Input, taps are used on both sides of the tuned circuit. A tap on the Inductance is made on the Antenna side and a tap is made on the Capacitance on the Transistor side for impedance matching. The RF Transistor Output is double tuned with mutual coupling (double peaks). This in combination with the single peak of the input circuit gives an essentially flat Bandwidth of 6 Mc for this stage.

A neutralizing capacitor is used in the base circuit as shown in Fig. 12 to prevent oscillation due to stray capacitance.

A gain of 14 dB is possible at 200 Mc with a circuit of this type but too much gain tends to make the Set unstable and hence the gain has been kept to be about 10 dB in our circuit. The gain on the lower channels tends to be higher than that on the higher channels, and so the damping resistors are inserted in the circuit of the lower channels to make the gain difference between the higher and lower channels within ± 1.5 dB.



(Fig. 12)

b. Mixer Circuit

The Mixer Transistor 2SA161 is emitter-grounded. The Impedance Matching is made by a capacitance divider in the same way as in the RF Amplifier. The Local Oscillation Signal is injected into the base of the transistor. The power dissipation in the mixer transistor is very much less (about $1/30$ — $1/50$) than the plate loss of the tube mixer. The voltage of the Local Oscillation Signal injected is about 0.2 Vrms, which is also much smaller ($1/10$ — $1/20$) than that in tube mixer. Furthermore, the G_m of the Transistor Mixer is high and hence the trouble with the mixer noise encountered in tube circuits are of no consequence here in our circuit. This circuit is also neutralized to prevent undesired oscillation.

c. Local Oscillator

The Local Oscillator uses a Colpits Circuit. This circuit is well suited for this use as it does not require a tap on the oscillator coil. The transistor (2SA161) is emitter grounded. The drift is kept within 200 Kc. As mentioned before, each oscillator coil is independent of the others so that the oscillation frequency can be adjusted from outside the Tuner by adjusting the screw type cores. The Cylindrical Fine Tuning Capacitors are separately shielded to prevent radiation from the set. The adjustable range of the Local Oscillation is approx. 1.6 Mc for Channel 2 and approx. 3 Mc for Channel 13.

2. UHF Tuner

The UHF Tuner consists of three sections, the Pre-selector, Mixer, Local Oscillator and all the circuit parts are enclosed in a shield case separated into three rooms by two shielding walls. Each section includes individual

Tuning Circuit using a metal strip which serves as an Inductance and a Tuning Capacitor driven by a single shaft. The metal strips in each section are electro-magnetically coupled for signal transmission. UHF/VHF switch is provided on the back side of the Tuner and is operated by the Switch Lever linked with the Channel Selector Shaft in the VHF Tuner. When the Channel Selector Knob is set to the position designated "U" the switch changes the circuit to receive UHF signal and simultaneously the Fine Tuning Knob of the VHF Tuner changes its function to drive the Tuning Capacitor Shaft in the UHF Tuner.

The UHF Tuner covers US UHF Channels 14—83 and converts the UHF signal into VHF signal of which center frequency is 74 Mc to be transmitted to the VHF Tuner. Each section of the UHF Tuner is as follows:

a. Pre-selector Section

The Pre-selector consists of a Tuning Circuit and is enclosed in the first room of the shield case. The Input Signal is transmitted to the metal strip from the lead wire for the Antenna Circuit.

b. Mixer Section

The Mixer Section enclosed in the second room consists of the Tuning Circuit same as that in the first room and the Mixer Circuit using one Esaki Diode. The Input Signal to the Pre-selector is transmitted to the metal strip in this section through a window made on the shielding wall between the rooms.

The Mixer Circuit receives the Input Signal from the metal strip in the Tuning Circuit in this section at the lead for the Esaki Diode which is also made of a piece of metal strip.


c. Local Oscillator Circuit

This section uses one PNP Mesa Type Germanium Transistor 2SA280 specially developed for this purpose by SONY and is enclosed in the third room. The Local Oscillation Signal is injected into the Esaki Diode in the Mixer Section at the metal strip lead extending from the second room through a window made on the shielding wall between the second and the third rooms. The transmission of the Local Oscillation Signal is made through the electro-magnetic coupling also.


Note :

To obtain satisfactory result, the Telescopic Antenna should be extended or retracted according to the Channel to be received. For the VHF Channels from 2 to 6, the Telescopic Antenna should be extended to its full length while for the VHF Channels from 7 to 13 and for the UHF Channels it should be fully retracted.

UHF Tuner



(Fig. 13-1)




(Fig. 13-2)

Signal Circuit Board Section

The Signal Circuit Board Section includes the Video IF, AGC, Sound Amplifier, Video Drive and Synchronizing Pulse Separation Circuits.

Block Diagram for Signal Circuit Board



(Fig. 14)

1. Video IF Section

The Video IF Section consists of three stages with three stagger tuned elements. The Video IF is 26.75 Mc while the Sound IF is 22, 25 Mc. The Bandwidth of this section is 3 Mc.

2. Automatic Gain Control

The Automatic Gain Control is made at the RF Amplifier Stage of the VHF Tuner and at the first stage of the Video IF Amplifier. For Video IF Amplifier, the Ultra-linear AGC of which operation is as explained below is used. The AGC signal is applied to the Base of X6 from the tap on the secondary winding of VIFT5 which feeds the Video IF Signal to the Video Detector. The Pulse generated at the Flyback Transformer is applied to the collector of X6 so that X6 operates only during the synchronizing period. The AGC Signal is amplified by X6 and rectified by D2 and then applied to the Base of X7 through a filter circuit. The time constant of this circuit is made very small so that the AGC response is extremely fast, thus permitting operation in cars where the signal level varies with extreme rapidity. Then the AGC current is amplified by X7 and applied to the Base of X1 which is connected in series with the Emitter of X2, the first VIF Amplifier. Since the Impedance between the Collector and the Emitter of X1 varies in accordance with the AGC current applied to the Base of X1, the negative feedback to X2 varies in amount corresponding to the variation of the AGC current. This means that the AGC current controls the gain at the first stage of the VIF Amplifier in which X2 is included. The main features of the Ultra-linear AGC are:

1) Quick Response

The AGC action is much faster than in conventional circuits because the Time Constant of the filter circuit is very small (approx. 2/1000 second) comparing to that in conventional one (1/10—1/20 second). Accordingly, stable reception is achieved even when the input signal level varies at a rate of 1/100 second.

2) Wider Effective Range

Effective AGC action is assured even when the input signal level varies in very wide range that may cause distortion in conventional circuits.

3) Noise Free Reception

The AGC action is hardly influenced by noise since the Synchronizing Pulse only of the signal is utilized.


On the contrary, in the ordinary peak value system, the AGC voltage varies considerably with the noise content of the Video Signal.

4) Effective AGC Action

The AGC action is quite effective due to higher gain in the AGC loop. Stability against the variation of the temperature and of power supply voltage is secured also.


The operation of the AGC on the VHF Tuner is as follows. See Fig. 15. The key point of this circuit is Diode D3 which conducts only when the Forward Bias Voltage exceeds 0.3 Volt. The potential at the negative terminal of the D3 is kept at 6 Volts with respect to the chassis by a voltage divider consisting of R329 (1K Ω) and R330 (1 K Ω) while the potential at the positive terminal varies according to the Collector Current of X3 in the VIF Amplifier. Therefore whether the D3 conducts or not depends upon the Collector Current of X3.

AGC on Tuner



(Fig. 15-1)

Basic Circuit of AGC for VHF Tuner



(Fig. 15-2)

a. Condition under which the D3 conducts:

Since the D3 conducts only when the Forward Bias Voltage exceeds 0.3 Volt, as mentioned above, the potential at the point D or B should be higher than 6.3 Volts. This means that the D3 starts to conduct as soon as the following relation is established.

$$I_{C \times 3} \geq \frac{6.3 (V)}{R_{302}}$$

where $I_{C \times 3}$ = Collector current of X3

When the D3 conducts $I_{C \times 3}$ starts to flow through both R302 and the D3 branch. Under this condition, the equivalent resistance of the branch D—D3—R330 is given by the following.

$$R_{eq} = \frac{E_D - E_K + E_K - E_G}{I_{D3}} = \frac{0.3 + (6 + 1000 \times I_{D3})}{I_{D3}}$$

where I_{D3} = Current flowing through D3

DC load for the Collector of X3 is considered as R302 and R_{eq} connected in parallel.

At zero input signal, $I_{C \times 3}$ remains maximum value of approx. 1mA while I_{D3} reaches its maximum value of approx. 700 μ A and the potential at the point D does not rise over approx. 7 Volts in any circumstance.

b. Condition under which the D3 cuts off:

If $I_{C \times 3}$ decreases to the value below 6.3 V/R302, the potential at the point B drops to the value below 6.3 Volts and the D3 cuts off.


c. Operation of X8 in the DC Amplifier:

The Emitter of X8 is directly connected to the Base of X201 in the RF Amplifier of the VHF Tuner of which potential is kept at 6.5 Volts. Therefore, the potential at the Emitter of X8 is kept at 6.5 Volts also. On the other hand, X8 does not conduct until the voltage between the Base and the Emitter exceeds 0.3 Volt. This means that X8 starts to conduct after the potential at its Base, that is the potential at the point B, drops to 6.2 Volts with respect to the chassis. In other words, AGC action does not effect

until the potential at the point B drops to 6.2 Volts. As apparent in the description mentioned above, AGC on the VHF Tuner effects only when the Collector current of X3 remains the values given by


$$I_{X3} \geq \frac{6.2(V)}{R_{302}}$$

The summary of the AGC action is as follows :



(Fig. 16)

Overall AGC Characteristics



(Fig. 17-2)

3. Sound Amplifier Section

The Sound Amplifier Section has two IF Stages, Ratio Detector and two Audio Amplifier Stages. However, the IF Amplifier can be considered substantially consisting of three stages because the Video Drive Stage works as a SIF amplifier also. The Output Stage uses the SEPP-OTL (Single-ended Push-pull No Output Transformer) system. The Speaker size is 2-3/4" x 4" and its impedance is 40Ω. There is a shield plate on SIFT3 to prevent the pulse from the Picture Tube Deflection Yoke to interfere with the sound. The maximum output is 320 mW at 10% distortion.

4. Video Driver

The Video Driver Circuit is of Emitter Follower Type (Collector Grounded). The Output Impedance is low and

this circuit has good frequency characteristics. The Video Signal and Synchronizing Pulse are separated at the Emitter of X14 while the sound is taken out at the Collector of the same transistor.

5. Synchronizing Pulse Separation

The Synchronizing Pulse is separated at X16 and the Vertical Pulse is taken out at its Collector.

This stage includes Noise Limiter for the Synchronizing Pulse. This permits stable operation of the set in a car without fear of interference from the ignition sparks and other pulsive noises.


Deflection Circuit Board and High-Voltage Block Sections

The Deflection Circuit Board contains the Video Output and the Vertical and Horizontal Deflection Circuits.

1. Video Output Circuit

A Mesa Silicon Transistor (2SC15, X15) is used in the Video Output Circuit. Over 50 Vpp of output is obtained from this circuit by supplying 80 Volts to the collector of X15. The Picture Tube requires 30 Vpp for sufficient contrast. The Contrast Control is obtained by varying the feedback current by means of the variable resistor VR2 which is located in the Emitter Circuit of X15. The gain of the stage can be varied by 24 dB with this control. The frequency response is almost flat to 3 Mc by the use of Shunt-peaking (L501-R508) and Series-peaking (L502-R509). Since the Video IF Bandwidth is 3 Mc and the beam spot of the Picture Tube is very small, a very sharp picture is obtained. The Horizontal resolution is more than 300 lines and the Vertical 400 lines. X15 is cut-off during Horizontal Blanking Period by the application of pulse from the Horizontal Deflection Circuit. The Horizontal Blanking Pulse is applied to the Emitter of X15 while the Vertical Blanking Pulse is applied to the first grid of the Picture Tube.

Block Diagram for Deflection Block



(Fig. 18)

2. Vertical Deflection Section

The Vertical Deflection Saw-tooth Wave is generated by blocking oscillation in the circuit of X18. It is then amplified by X19 and X20 and applied to the Vertical Deflection Yoke of the Picture Tube. Vertical Amplitude and Linearity are adjusted by Variable Resistors VR7 and VR8 in the Base Circuit of X19. The Back Pulse is suppressed by Clipping Circuit using a Diode D10 in the collector circuit of X20, the Vertical Output Transistor. The Pulse is taken out at the terminal of D10.

The heat generated in X20 is dissipated through a large heat sink and the variation of the characteristics due to the temperature difference is compensated by the thermistor located in the Base Circuit of X20. For the effective compensation, the thermistor is placed in a cavity provided on the bottom of X20. The Variable Resistor VR9 in the Base Circuit of X20 serves to adjust the operating point of X20 and it is not necessary to re-adjust it except when X20 is replaced.

3. Horizontal Deflection Section

The Horizontal Deflection Pulse is generated by Blocking Oscillation in the circuit of X21 and is amplified by X23 which drives X24 and X25. X24 and X25 generate the Saw-tooth Wave to drive the Horizontal Deflection Coil. The Horizontal Output Transistors X24 and X25 are also connected to the Horizontal Output Transformer and supply the input for the High Voltage Circuit with the Flyback Pulse during Cut-off. All of the transistors except X22 in the Horizontal Deflection Circuit are of the Silicon Type. This assures stable operation almost free from temperature effects.

Two Diodes D12 and D13 connected to the tap of the Horizontal Output Transformer operate as a damper to improve the linearity of the wave form which has tendency of being affected by high collector saturation resistance in the silicon transistors.

The capacitor C815 connected in series with the Horizontal Deflection Coil serves to compensate the deflection current to correct deteriorated linearity due to curvature of the screen of the Picture Tube.

For AFC, the negative pulse is taken from the collector of X23, the Horizontal Driver and is integrated after it is delayed by L601. The Saw-tooth Reference Wave obtained through this process is applied to the Base of X21 to control the blocking oscillation.


4. High Voltage Block

The High Voltage Block consists of the Horizontal Output Transformer and the High Voltage Rectifier. All are housed together in one metal case. The Flyback Pulse is stepped up, rectified and resulting voltage of 9 KV, 400 V and 80 V are applied to the Anode, Second Grid of the Picture Tube and the Video Transistor X15 respectively. The 9 KV is obtained by means of the three rectifier tubes in voltage tripler circuit.

5. Focus Adjustment


The Voltage for the Second Grid of the Picture Tube goes also to the Potentiometer VR10. The focusing Voltage is obtained from this Potentiometer and is variable between 0 and 230 V.

Diode Clipping Circuit




(Fig. 19)

High Voltage Block



(Fig. 20)




(Fig. 21)

Power Supply Section


117V AC is converted to 12V DC by four Selenium Rectifiers in a Bridge Connection as shown in Fig. 22. Power Transformer with oriented core is used in this set to prevent any trouble from Leakage Flux. The primary winding of the Power Transformer is grounded to the chassis through two 1.5MΩ resistors in accordance with the safety measure provided in the specifications LA, CSA etc. of the United States and Canada. Accordingly, one may feel a slight electrical shock when he touches the Cabinet of the set operated with AC Power Supply. This is harmless and is not to be mistaken as an indication of trouble with the set.

Connection of the Power Supply



(Fig. 22)

Charging Adapter




(Fig. 23)

Method of Disassembling the Set


To Open the Back Cover of the Cabinet (Remove the five screws shown in the Fig. 24.)

To Remove the Front Control Panel

1. Pull out all the Control Knobs straight. The Channel Selector Knob can be removed by pulling the Fine Tuning Knob out.
2. Place the Set with the side surface down and remove two screws 1 and 2 on the bottom of the Cabinet. See the Fig. 25.




(Fig. 24)



(Fig. 25)


3. Raise up the Front Control Panel with the finger at the hole for the Channel Selector Knob as shown in the Fig. 26.




(Fig. 26)

To Remove the Tuner Block


1. Open the Back Cover of the Cabinet.
2. Remove the Signal Circuit Board (refer to "To Check and to Remove the Signal Circuit Board").
3. Remove the External Antenna Jack from the Cabinet by loosening the holding screw located below the same. See the Fig. 27.
4. Unsolder the Shielded Cable extending from the Telescopic Antenna at the upper terminals of the jack. See Fig. 27.
5. Unsolder the Orange wire at the terminal of the 5-P Tie-points. See the Fig. 27.
6. Remove the Front Control Panel and push the Neon Lamp out toward the left to disengage from the holder. See the Fig. 28.
7. Remove the two screws 1 and 2 in the Fig. 28. The Tuner Block can now be taken out from the Cabinet by pulling forward.
8. To separate the Tuner Block completely from the Cabinet, unsolder the two wires, one is Red and the other Yellow, at the terminals on the back of the Tuner Block.




(Fig. 27)



(Fig. 28)




(Fig. 29)




(Fig. 30)

9. To separate the UHF Tuner from the VHF Tuner, remove the Shielding Plate of the UHF/VHF Switch on the back of the Tuner Block by removing the two screws 1 and 2 in the Fig. 31 and unsolder the Black wire extending from the VHF Tuner at the terminal of the switch.
10. Remove the four screws 3 and 4 in the Fig. 31 and 1 and 2 in the Fig. 32.




(Fig. 31)




(Fig. 32)

To Remove the Potentiometer for Volume Control, Contrast Control, Brightness Control, Horizontal Hold and Vertical Hold

1. Remove the Front Control Panel.
2. Remove the four screws 1, 2, 3 and 4 shown in the Fig. 33.
3. Pull out the Holding Plate for Potentiometer from the cabinet. Be careful not to pull it too much to prevent the wires connected to the Potentiometers from damage.




(Fig. 33)



(Fig. 34)

To Check and to Remove the Signal Circuit Board

1. Remove the two screws 1 and 2 in the Fig. 35.
2. To Check the printed side of the Circuit Board, pull its left edge. The Circuit Board will swing around the axis of the Multi-jack located at the right hand side of the Circuit Board. Be carefull not lose two small rubber cushions on the printed side of the Circuit Board at the screw holes.
3. To Remove the Circuit Board, pull out the Shielded Cables, one for the IF Input and the other for the Keying Pulse Input, from the pins on the Circuit Board.
The pin designated with the Red Mark is for the Inner Conductor of the IF Input Cable while the one designated with the + Mark is for the Inner Conductor of the Keying Pulse Input Cable.
4. Then pull out the Circuit Board toward the left.



(Fig. 35)

To Check and to Remove the Deflection Circuit Board

1. Remove the three screws 3, 4 and 5 in the Fig. 35.
2. To Check the printed side of the Circuit Board, pull its right edge. The Circuit Board will swing around the axis of the Multi-jack located at the left hand side.
3. To Remove the Circuit Board, pull out the eight Lead Wires from the pins on the Circuit Board. The colors of the Lead Wires are as follows :

Marking for the pins	R	O	BN	BU	W	Y	GN	GY
Colors of the Lead Wires	Red	Orange	Brown	Blue	White	Yellow	Green	Gray


4. Then pull out the Circuit Board toward the right.

To Remove the Chassis from the Cabinet

The Chassis is mounted with the High Voltage Block, Power Transformer, Filter Choke Coil, Selenium Rectifier and Filter Condensers.

To Remove the Chassis


1. Pull out all the Control Knobs.
2. Open the Back Cover of the Cabinet and Remove the Signal Circuit Board and the Deflection Circuit Board.
3. Remove the two screws 3 and 4 on the bottom of the Cabinet. See the Fig. 25.
4. Unsolder the following Shielded Cable and the Lead Wires. See the Fig. 36.
 - a. Shielded Cable at the bottom of the Telescopic Antenna (Position A).
 - b. Two Black Wires which are the Grounding Wire for the Picture Tube and the Lead Wire for the Speaker respectively at the Tie-points located near the Fuse (Position B and C).
 - c. White Wire at the Speaker Terminal. (position D)
5. Remove the External Antenna Jack by loosening the securing screw.
6. Pull out the Anode Connector and the Socket from the Picture Tube.
7. Remove the two screws 1 and 2 and pull out the Chassis from the Cabinet with a slight lifting motion. See the Fig. 36.
8. To Separate the Chassis completely from the Cabinet, Unsolder the Red and the Green Lead Wires extending from the Deflection Yoke on the Picture Tube at their tips where the same colored Lead Wires are jointed respectively.




(Fig. 36)

Front View of Chassis

Back View of Chassis



(Fig. 37)



(Fig. 38)

To Remove the High Voltage Block

Remove the two Philips screws beneath the Multi-jack for Deflection Circuit Board.


To Remove the Speaker (See the Fig. 39)

1. Remove the four screws 1, 2, 3 and 4 while holding the Speaker with hand.
2. Remove the Speaker Grille by pushing it straight up to disengage from the Earphone Jack. The Speaker can be removed together with the Earphone Jack.

Note :

To attach the Speaker Grill to the Cabinet do it according to the following procedures to prevent the Earphone Jack from being damaged.


1. At first, insert the Earphone Jack into its position matching the groove of the Earphone Jack to the edge of the hole on the Cabinet.
2. Tilt the Earphone Jack as shown in the Fig. 39.
3. Fit the gain at the lower end of the Speaker Grille to the Earphone Jack.
4. Bring the Speaker Grille to the position by pushing its upper part against the Cabinet.



(Fig. 39)

To Remove the Telescopic Antenna

1. Open the Back Cover of the Cabinet.
2. Remove the Signal Circuit Board.
3. Unsolder the Shielded Cable at the bottom of the Telescopic Antenna.
4. Remove the two screws 1 and 2 in the Fig. 40
5. Push the Antenna into the Cabinet. The Antenna will be removed with the Antenna Bushing left on the top of the Cabinet.



(Fig. 40)


To Remove the Picture Tube

1. Remove the Chassis from the Cabinet.
2. Remove the Deflection Yoke by loosening the screw located on the brass Holding Band.
3. Place the Set with its Front Side down. This is quite important to prevent the Picture Tube from damage due to accidental drop that might be happened in the following step.
4. Remove the four screws 1, 2, 3 and 4 in the Fig. 41.
5. Lift the Cabinet and the Picture Tube will remain on the table together with Mask.
6. Remove the Picture Tube Holding Ring from the tube by loosening the nut shown in the Fig. 42


7. Remove the four screws 5, 6, 7 and 8 shown in the Fig. 43.

Note :


The position of the Anode Terminal of the Picture Tube should be determined according to the Fig. 43 when the Tube is to be mounted.



(Fig. 41)



(Fig. 42)



(Fig. 43)

Trouble Shooting

by Replacement of the Defective Block

Provisions have been made in this TV for easy servicing. The main part of the set is made of four Blocks of the Tuner, the Signal Circuit Board, the Deflection Circuit Board and the High Voltage Block. Each of these Blocks has complete interchangeability and hence the servicing can be performed by simply replacing the defective Block with a new one.

The way of judging which Block is defective and the method of replacing the Block will be given below.

Replacement Blocks :

Tuner, Signal Circuit Board, Deflection Circuit Board and High Voltage Block

Tools and Meters :

Multi-meter of internal resistance around $20\text{ K}\Omega/\text{V}$

Cord with Clips.....2 pcs.

Electrolytic Capacitor, $3\mu\text{F}$, 500WV or more1 pc.

Resistor around $15\text{ K}\Omega$ 1 pc.

Screw Drivers

For 3 mm Screws, Philips and ordinary

For 2.6 mm Screws, Philips and ordinary

No. 3 for watch for adjustment of local oscillator

Tweezers

Soldering Iron

Raster

1. No Raster and No Sound

Suspectable Item : * Power Supply

Check the Power Supply. If there is no trouble in the Power Supply, there must be two or more Blocks defective. Then proceed with the checking according to the following.

2. No Raster

See first whether the Neon Lamp is lit.

1) The Neon Lamp is OFF

Suspectable Items : * Deflection Circuit Board
* High Voltage Block

a) Replace the Deflection Circuit Board.


b) If the Neon Lamp is not lit after a), replace the High Voltage Block.

2) The Neon Lamp is lit.

Suspectable Items : * High Voltage Block
* Picture Tube
* Brightness Control Circuit

a) See whether the filament of the Picture Tube is ON. If the filament is OFF, check the Socket for the Picture Tube. The pins for the filament are Nos. 3 and 4.

b) If the filament is ON, the trouble is probably with the High Voltage Block. Before proceeding on to replace the High Voltage Block, see whether the cathode circuit of the Picture Tube (the Brightness Control Circuit) is all right.



(Fig. 44)

To do this, measure the cathode voltage (pin Y on the Deflection Circuit Board) from the copper side of the Deflection Circuit Board (refer to the Fig. 44). If this voltage is varied between 0 and 15 to 75 Volts by an adjustment of the Brightness Control, the cathode circuit is all right and the High Voltage Block is to be replaced.

- c) If the voltage is abnormal, the Brightness Control Circuit on the Deflection Circuit Board must be checked.
- d) If the Raster still does not appear after replacing the High Voltage Block, the Picture Tube may be defective.

CAUTION

NEVER ATTEMPT TO CHECK THE HIGH VOLTAGE (9 KV) CIRCUIT BY SPARK TEST.

The High Voltage is often tested by a Spark Test. But, in the Transistor TV, this is likely to cause damage not only to the Horizontal Deflection Circuit but also to other seemingly not related parts of the set. Especially, the High Voltage Spark will adversely affect the transistors on the Signal Circuit Board because of the Pulse AGC Circuit employed.

3. Raster appears but is abnormal

First of all check the 12V DC Supply.

1) Too small Raster

Suspectable Item : * Deflection Circuit Board
Replace the Deflection Circuit Board.

2) Raster is dark.

Suspectable Items : * Picture Tube
* High Voltage Block

- a) When the Raster size is normal but is not bright enough, the trouble is almost certainly with the Picture Tube.
- b) When the Raster spreads out and gets dark while the Brightness is meant to be increased, the trouble is with the reduced emission of the High Voltage Rectifier Tube.

Video Output and Synchronization

1. No Picture (Sound is normal)

Suspectable Items :

- * Deflection Circuit Board
- * Signal Circuit Board

Check the Video Output Circuit Board as follows :

Apply AC test voltage taken from the secondary winding of the Power Transformer through a 15K Ω Resistor and a 3 μ F, 500WV or more Electrolytic Capacitor, to the Terminal 12 (the Input terminal to the Video Output Circuit) of the Deflection Circuit Board as shown in the Fig. 45. If the AC hum appears on the Picture Tube, replace the Signal Circuit Board. If not, replace the Deflection Circuit Board.

2. Failure of Synchronization

1) Failure of both Horizontal and Vertical Synchronization

Suspectable Items :

- * Deflection Circuit Board
- * Signal Circuit Board

Measure the voltage at the Terminal 11 of the Signal Circuit Board and decide whether the trouble is with the Signal Circuit Board or with the Deflection Circuit Board. The normal value of the voltage is around 2.5 Volts. If the voltage is more than 2.5 V, replace the Signal Circuit Board. If it is abnormally low, replace the Deflection Circuit Board.

2) Failure of either Horizontal or Vertical Synchronization alone

Suspectable Item :

- * Deflection Circuit Board

In this case, replace the Deflection Circuit Board.

3. No Picture and No Sound

Suspectable Items :

- * Tuner
- * Signal Circuit Board

a) Replace the Signal Circuit Board and see the result.


b) Apply the output from another tuner to the input Terminal of the Signal Circuit Board as shown in the Fig. 45 and see the result. The power of this tuner is to be taken from the set with a length of cord with clips.

4. Only one or few Channels are defective

Suspectable Items :

- * Tuner
- * Signal Circuit Board
- * Deflection Circuit Board

For trouble like low contrast, poor signal to noise ratio and poor resolution, replace the Signal Circuit Board first. Then, if the signal to noise ratio is still poor, replace the Tuner. If the contrast is low, replace the Deflection Circuit Board.



(Fig. 45)

Sound (Picture is normal)

1. No Sound

Suspectable Items :

- * Speaker
- * Signal Circuit Board

Listen with the earphone.

a) Check the Speaker and the Earphone Jack if sound is heard from the earphone.

b) If still no sound can be heard, replace the Signal Circuit Board.

2. Sound is distorted.

Suspectable Items :

- * Speaker
- * Signal Circuit Board

Judge by hearing the sound whether the trouble is with the defective Speaker. If the trouble is not caused by the Speaker, replace the Signal Circuit Board.

3. Buzzing

Suspectable Items :

- * Antenna
- * Fine Tuning
- * SIFT3
- * Signal Circuit Board

a) If the Buzz appears only on some specific Channel, the trouble is not with the set itself. Adjust the Antenna and the Fine Tuning.

b) If the Buzz appears on all Channels, adjust the Blue Core of SIFT3.

c) Then, if the Buzz still exists, replace the Signal Circuit Board.


4. Other troubles with sound

Suspectable Item :

- * Signal Circuit Board

For other troubles with the Sound, replace the Signal Circuit Board.


Adjustment of the Local Oscillator Frequency




Turn the screw type core of the Oscillator Coil in the Tuner. The Frequency increases as the core is turned clockwise.

(Fig. 46)


Signal Circuit Board



Deflection Circuit Board




Deflection Circuit Board



Mounting Diagram

Deflection Circuit Board—



- Jumper wire on printed side (PVC Wire, I6/O16, Black)
Jumper wire on Mounted side (Tinned Copper Wire, I/O6)
Jumper wire on Mounted side (PVC Wire, I/O64, Yellow)

Note.

1. Resistors designated X show $1/4L$ type.
2. Resistor below 10Ω are of wire-wound type.
3. Resistors and Capacitors designated Δ are to be adjusted.

—Signal Circuit Board—




—Signal Circuit Board—




— 30 —


—Pulse AGC Circuit—




—AFC AMP.—




—Ver. Def. Circuit—



—Hor. Def. Circuit—



Schematic Diagram



Electrical Parts List (A)

Part No.	Symbol	Description	Part No.	Symbol	Description
		Transistor	1-902-601-11	L ₂₁₅	Poly-urethan Wire 25mm
X ₁₀₁		2-80 (UHF OSC)	X-44026-41-1		Rotor Coil Ass'y
X ₂₀₁		2SA163 (VHF RF)	1-403-427-11	VIFT ₂	Video IF Transformer (23.75 Mc)
X ₂₀₂		2SA161 (VHF MIX)	1-403-428-11	VIFT ₃	Video IF Transformer (26.45 Mc)
X ₂₀₃		2SA163 (VHF OSC)	1-403-429-11	VIFT ₄	Video IF Transformer (24.3 Mc)
X ₁		2SA70 (Imp Conv)	1-403-430-11	VIFT ₅	Video IF Transformer (25.1 Mc)
X ₂		2SA70 (1st VIF Amp)	1-403-419-02	VIFT ₆	Video IF Transformer (26.75 Mc)
X ₃		2SA70 (2nd VIF Amp)	1-403-314-11	SIFT ₁	Sound IF Transformer
X ₄		2SA70 (3rd VIF Amp)	1-403-315-11	SIFT ₂	Sound IF Transformer
X ₅		2SA70 (4th VIF Amp)	1-403-313-11	SIFT ₃	Sound IF Transformer (Detector)
X ₆		2SA70 (AGC Amp)	1-403-420-02	Det	Video Detector Block
X ₇		2SC73 (DC Amp)	1-403-431-11	AGC Det	AGC Detector Block
X ₈		2SB381 (DC Amp)	1-409-022-11	Trap ₁	Trap Coil (22.25 Mc)
X ₉		2SA124 (2nd SIF Amp)	1-409-023-11	Trap ₂	Trap Coil (28.25 Mc)
X ₁₀		2SA121 (3rd SIF Amp)	1-409-024-11	Sound	Sound Signal Trap Coil
X ₁₁		2SD64 (AF Drive)		Trap	
X ₁₂		2SB382 (AF Power Amp)	1-423-067-11	SDT	Sound Driver Transformer
X ₁₃		2SB382 (AF Power Amp)	1-435-008-11	VBT	Vertical Blocking Transformer
X ₁₄		2SA60 (Video Drive & 1st SIF Amp)	1-435-007-12	HBT	Horizontal Blocking Transformer
X ₁₅		2SC15 (Video Out)	1-437-002-00	HDT	Horizontal Driver Transformer
X ₁₆		2SA60 (Sync Sep & Noise Limit)	1-437-051-11	BT	Balance Transformer for Hor. Power
X ₁₇		2SD65 (Sync Split)	1-413-005-11	L ₈₀₁	Stabilizing Coil for Hor. Sweep
X ₁₈		2SB381 (Ver Osc)	1-421-013-11	L ₈₀₂	Horizontal Choke Coil (25μH)
X ₁₉		2SD65 (Ver Drive)	1-407-049-11	L ₅₀₁	Micro Inductor (270μH)
X ₂₀		2SB382 (Ver Power)	1-407-030-11	L ₅₀₂	Micro Inductor (150μH)
X ₂₁		2SC115 (Hor Osc)	1-441-085-11	PT	Power Transformer
X ₂₂		2SD65 (Hor Buff)	1-421-014-11	BCH	Filter Choke Coil for Power Supply
X ₂₃		2SC140 (Hor Drive)	1-421-107-11	VCH	Vertical Output Choke Coil
X ₂₄		2SC41 (Hor Power)	1-407-052-11	L ₈₀₁	Micro Inductor (470μH)
X ₂₅		2SC41 (Hor Power)	1-407-030-11	L ₉₀₁	Micro Inductor (150μH)
		Diode	1-513-188-12		Input Signal (UHF, VHF) Selector Switch.
D ₁₀₁		1T13 (UHF Mixer)			Potentiometer
D ₁		1T261J (Built in Det Block)	1-221-388-12	VR ₁	Volume Control 5 KΩ
D ₂		1T261J (Built in Det Block)	1-221-386-11	VR ₂	Contrast Control 3 KΩ
D ₃		1T22G	1-221-384-11	VR ₃	Brightness Control 250 KΩ
D ₄		1T23G	1-221-385-11	VR ₄	Horizontal Hold 10 KΩ
D ₅		1T23G	1-221-387-11	VR ₅	Vertical Hold 2 KΩ
D ₆		1T22G	1-221-355-11	VR ₆	AGC Setting 3 KΩ (Semi-fixed)
D ₇		1T22G	1-221-389-11	VR ₇	Vertical Height 5 KΩ (Semi-fixed)
D ₈		1T22A	1-221-389-11	VR ₈	Vertical Linearity 5 KΩ (Semi-fixed)
D ₉		1T22A	1-221-304-11	VR ₉	Vertical Bias 10 KΩ (Semi-fixed)
D ₁₀		2SC40	1-221-391-11	VR ₁₀	Focus Control 600 KΩ (Semi-fixed)
D ₁₁		1T22G	1-221-390-11	VR ₁₁	Hor. Frequency 3 KΩ (Semi-fixed)
D ₁₂		S2A30			Tube & Rectifiers
D ₁₃		S2A30	731270900	CRT	Picture Tube
D ₁₄		SD-1LA	1-525-039-00	HV Rect.	High Voltage Rectifier (1DK1)
D ₁₅		SD-1LA			Encapsulated Component
1-531-105-11	Se	Selenium Rectifier.	1-101-537-11	CR ₃₀₁	1.5 KΩ, 0.01 μF, 0.01 μF
		Thermistor	1-101-406-01	CR ₃₀₂	1.2 KΩ, 0.01 μF, 0.01 μF
8-690-003-00	Th ₁	S-90	1-101-406-01	CR ₃₀₃	1.2 KΩ, 0.01 μF, 0.01 μF
-005-00	Th ₂	S-300	1-101-406-01	CR ₃₀₄	1.2 KΩ, 0.01 μF, 0.01 μF
		Coil & Transformers	1-101-406-01	CR ₄₀₁	1.2 KΩ, 0.01 μF, 0.01 μF
1-425-075-11	L ₂	Coil	1-101-536-11	CR ₄₃₂	3.3 KΩ, 3.3 KΩ, 500pF, 500pF
1-425-076-11	L ₄	Coil			Resistor
1-407-035-11	L ₅	Choke Coil	1-204-156-00	R ₁	750 Ω, RD _{1/32} L, Carbon
1-409-027-11	L ₂₀₁	IF Trap (A)	1-203-977-00	R ₂	5 KΩ, " " "
1-425-083-11	L ₂₀₂	RF Coil (D)	1-203-184-00	R ₃	2.2 KΩ, " " "
1-425-049-11	L ₂₀₃	RF Coil (A)		R ₄	—deleted—
1-425-050-11	L ₂₀₄	RF Coil (B)	1-204-110-11	R ₅	330 Ω, RD _{1/32} L, Carbon
1-409-028-11	L ₂₀₅	IF Trap (B)	1-203-889-11	R ₁₀₁	27 KΩ, RD _{1/16} L, "
1-403-432-11	L ₂₀₆	IF Trans.	1-204-103-11	R ₂₀₁	2.7 KΩ, RD _{1/32} SL, "
1-425-104-11	L ₂₀₇	Compensation Coil for Fine Tuning Capacitor	1-203-192-11	R ₂₀₂	15 KΩ, RD _{1/16} L, "
1-902-488-11	L ₂₀₈	Poly-urethan Wire 36mm	1-204-101-11	R ₂₀₃	240 Ω, RD _{1/32} SL, "
1-902-489-11	L ₂₀₉	Poly-urethan Wire 10mm	1-204-152-11	R ₂₀₄	1 KΩ, " " "
1-407-035-12	L ₂₁₃	Micro Inductor			
1-407-052-12	L ₂₁₄	Micro Inductor			

Part No.	Symbol	Description	Part No.	Symbol	Description
1-204-104-11	R ₂₀₅	4.7 K Ω , RD $\frac{1}{32}$ SL, Carbon	1-203-462-11	R ₄₁₈	7 Ω , RD $\frac{1}{4}$ L, Carbon
1-203-193-11	R ₂₀₆	18 K Ω , RD $\frac{1}{16}$ L, "	1-203-461-00	R ₄₁₉	7 Ω , RD $\frac{1}{8}$ RL, "
1-204-102-11	R ₂₀₇	1 K Ω , RD $\frac{1}{32}$ SL, "	1-203-422-00	R ₄₂₀	1.5 K Ω , RD $\frac{1}{16}$ RL, "
1-204-102-11	R ₂₀₈	1 K Ω , " "	1-203-780-00	R ₄₂₁	1.2 K Ω , " "
1-204-102-11	R ₂₀₉	1 K Ω , " "	1-203-361-00	R ₄₂₂	470 Ω , " "
1-204-103-11	R ₂₁₀	2.7 K Ω , " "	1-203-423-00	R ₄₂₃	2.2 K Ω , " "
1-204-190-11	R ₂₁₁	10 K Ω , RD $\frac{1}{16}$ L, "	1-203-148-00	R ₄₂₄	47 Ω , RD $\frac{1}{4}$ L, "
1-204-103-11	R ₂₁₂	2.7 K Ω , RD $\frac{1}{32}$ SL, "	1-203-370-00	R ₄₂₅	2.2 K Ω , RD $\frac{1}{8}$ RL, "
1-204-041-11	R ₂₁₃	240 Ω , RD $\frac{1}{16}$ L, "	1-203-386-00	R ₅₀₁	15 K Ω , " "
1-204-853-11	R ₂₁₄	1.2 K Ω , " "	1-203-386-00	R ₅₀₂	15 K Ω , " "
1-204-104-11	R ₂₁₅	4.7 K Ω , RD $\frac{1}{32}$ SL, "	1-203-778-00	R ₅₀₃	2.4 K Ω , " "
1-204-109-11	R ₂₁₆	1.5 K Ω , " "	1-203-397-00	R ₅₀₄	82 K Ω , " "
1-204-103-11	R ₂₁₇	2.7 K Ω , " "	1-203-408-00	R ₅₀₅	18 K Ω , " "
1-204-103-11	R ₂₁₈	2.7 K Ω , " "			(to be adjusted)
1-204-105-11	R ₂₁₉	5.1 K Ω , " "	1-203-820-00	R ₅₀₆	43 Ω , " "
1-204-104-11	R ₂₂₀	4.7 K Ω , " "	1-203-370-00	R ₅₀₇	2.2 K Ω , " "
1-204-105-11	R ₂₂₁	5.1 K Ω , " "	1-203-068-00	R ₅₀₈	8.2 K Ω , RD $\frac{1}{4}$ L, "
1-203-875-00	R ₃₀₁	120 Ω , RD $\frac{1}{16}$ L, "	1-203-802-00	R ₅₀₉	9.1 K Ω , RD $\frac{1}{8}$ RL, "
1-203-388-00	R ₃₀₂	27 K Ω , RD $\frac{1}{8}$ RL, "	1-203-123-00	R ₅₁₀	120 K Ω , RD $\frac{1}{4}$ L, "
1-203-372-00	R ₃₀₃	2.7 K Ω , " "	1-203-352-00	R ₅₁₁	22 Ω , RD $\frac{1}{8}$ RL, "
1-203-190-00	R ₃₀₄	10 K Ω , RD $\frac{1}{16}$ L, "	1-203-097-00	R ₅₁₂	56 K Ω , RD $\frac{1}{4}$ L, "
1-203-891-00	R ₃₀₅	22 K Ω , " "	1-203-316-00	R ₆₀₁	510 Ω , RD $\frac{1}{8}$ RL, "
1-203-368-00	R ₃₀₆	1.2 K Ω , RD $\frac{1}{8}$ RL, "	1-203-368-00	R ₆₀₂	1.2 K Ω , " "
	R ₃₀₇	—deleted—	1-203-390-00	R ₆₀₃	33 K Ω , " "
1-203-414-00	R ₃₀₈	47 Ω , RD $\frac{1}{8}$ RL, Carbon	1-203-326-00	R ₆₀₄	690 K Ω , " "
1-203-190-00	R ₃₀₉	10 K Ω , RD $\frac{1}{16}$ L, "	1-203-378-00	R ₆₀₅	5.6 K Ω , " "
	R ₃₁₀	—deleted—	1-203-383-00	R ₆₀₆	10 K Ω , " "
1-203-414-00	R ₃₁₁	47 Ω , RD $\frac{1}{8}$ RL, "			—deleted—
1-203-368-00	R ₃₁₂	1.2 K Ω , " "	1-203-316-00	R ₆₀₈	510 Ω , RD $\frac{1}{8}$ RL, Carbon
1-203-373-00	R ₃₁₃	3.3 K Ω , " "	1-203-316-00	R ₆₀₉	510 Ω , " "
1-203-368-00	R ₃₁₄	1.2 K Ω , " "	1-203-368-00	R ₆₁₀	1.2 K Ω , " "
1-203-370-00	R ₃₁₅	2.2 K Ω , " "	1-203-368-00	R ₆₁₁	1.2 K Ω , " "
	R ₃₁₆	—deleted—	1-203-357-00	R ₆₁₂	100 Ω , " "
	R ₃₁₇	—deleted—	1-203-761-00	R ₆₁₃	910 Ω , " "
1-203-878-00	R ₃₁₈	3.9K Ω , RD $\frac{1}{16}$ RL, "	1-203-361-00	R ₆₁₄	470 Ω , " "
1-203-383-00	R ₃₁₉	10 K Ω , RD $\frac{1}{8}$ RL, "	1-203-383-00	R ₆₁₅	10 K Ω , " "
1-203-357-00	R ₃₂₀	100 Ω , " "	1-203-368-00	R ₆₁₆	1.2 K Ω , " "
1-203-376-00	R ₃₂₁	4.7 K Ω , " "	1-203-378-00	R ₆₁₇	5.6 K Ω , " "
1-203-370-00	R ₃₂₂	2.2 K Ω , " "	1-203-367-00	R ₆₁₈	1 K Ω , " "
1-203-405-00	R ₃₂₃	1.5 K Ω , " "	1-203-701-00	R ₇₀₁	1.2 K Ω , RD $\frac{1}{4}$ L, "
1-203-414-00	R ₃₂₄	47 Ω , " "	1-203-039-00	R ₇₀₂	1.5 K Ω , " "
1-203-383-00	R ₃₂₅	10 K Ω , " "	1-203-367-00	R ₇₀₃	1 K Ω , RD $\frac{1}{8}$ RL, "
1-203-361-00	R ₃₂₆	470 Ω , " "	1-203-415-00	R ₇₀₄	150 Ω , " "
1-203-414-00	R ₃₂₇	47 Ω , " "	1-203-378-00	R ₇₀₅	5.6 K Ω , " "
1-203-857-00	R ₃₂₈	620 Ω , " "	1-203-372-00	R ₇₀₆	2.7 K Ω , " "
1-203-031-00	R ₃₂₉	1 K Ω , RD $\frac{1}{4}$ L, "	1-203-367-00	R ₇₀₇	1 K Ω , " "
1-203-367-00	R ₃₃₀	1 K Ω , RD $\frac{1}{8}$ RL, "	1-203-368-00	R ₇₀₈	1.2 K Ω , " "
1-203-414-00	R ₃₃₁	47 K Ω , " "	1-207-019-00	R ₇₀₉	3 Ω , RW $\frac{1}{4}$ RL, Wire Wound
1-203-380-00	R ₄₀₁	6.2 K Ω , " "	1-203-412-00	R ₇₁₀	390 Ω , RD $\frac{1}{8}$ RL, Carbon
1-203-373-00	R ₄₀₂	3.3 K Ω , " "	1-203-415-00	R ₇₁₁	150 Ω , " "
1-203-373-00	R ₄₀₃	3.3 K Ω , " "	1-203-373-00	R ₇₁₂	3.3 K Ω , " "
1-203-372-00	R ₄₀₄	2.7 K Ω , " "	1-203-381-00	R ₇₁₃	6.8 K Ω , " "
1-203-381-00	R ₄₀₅	6.8 K Ω , " "	1-203-373-00	R ₇₁₄	3.3 K Ω , " "
1-203-634-00	R ₄₀₆	33 K Ω , RD $\frac{1}{16}$ RL, "	1-207-014-00	R ₇₁₅	2 Ω , RW $\frac{1}{4}$ RL, Wire Wound
1-203-148-00	R ₄₀₇	47 Ω , RD $\frac{1}{4}$ L, "	1-203-381-00	R ₇₁₆	6.8 K Ω , RD $\frac{1}{8}$ RL, Carbon
1-203-388-00	R ₄₀₈	27K Ω , RD $\frac{1}{8}$ RL, "	1-201-596-00	R ₇₁₇	3.3 M Ω , RC $\frac{1}{2}$ L, Composition
1-203-378-00	R ₄₀₉	5.6 K Ω , " "	1-203-363-00	R ₇₁₈	560 Ω , RD $\frac{1}{8}$ RL, Carbon
1-203-405-00	R ₄₁₀	1.5 K Ω , " "	1-203-363-00	R ₇₁₉	560 Ω , " "
1-203-704-00	R ₄₁₁	3 Ω , " "	1-203-443-00	R ₈₀₁	3 K Ω , " "
1-203-011-00	R ₄₁₂	100 Ω , RD $\frac{1}{4}$ L, "	1-203-857-00	R ₈₀₂	620 Ω , " "
1-203-373-00	R ₄₁₃	3.3 K Ω , RD $\frac{1}{8}$ RL, "	1-203-760-00	R ₈₀₃	430 Ω , " "
1-203-380-00	R ₄₁₄	6.2 K Ω , " "	1-203-367-00	R ₈₀₄	1 K Ω , " "
1-203-356-00	R ₄₁₅	75 Ω , " "	1-203-360-00	R ₈₀₅	330 Ω , " "
1-203-443-00	R ₄₁₆	3 K Ω , " "	1-207-019-00	R ₈₀₆	1~8.2 Ω , RW $\frac{1}{4}$ RL, Wire Wound
1-203-461-00	R ₄₁₇	7 Ω , RD $\frac{1}{4}$ L, "			(to be adjusted)

Part No.	Symbol	Description	Part No.	Symbol	Description
1-203-384-00	R ₉₀₇	12 K Ω , RD $\frac{1}{8}$ RL, Carbon	1-121-106-11	C ₃₁₁	5 μ F 6WV Electrolytic
1-203-405-00	R ₉₀₈	1.5 K Ω , " "	1-101-010-11	C ₃₁₂	2pF Ceramic
1-203-399-00	R ₉₀₉	100 K Ω , " "	1-121-106-01	C ₃₁₃	5 μ F 6WV Electrolytic
1-203-031-00	R ₉₁₀	1 K Ω , RD $\frac{1}{4}$ L, "	1-101-004-01	C ₃₁₄	0.01 μ F 50WV Ceramic
1-203-867-00	R ₉₁₁	390 K Ω , RD $\frac{1}{8}$ RL, "	1-121-135-01	C ₃₁₅	50 μ F 6WV Electrolytic
1-203-399-00	R ₉₁₂	100 K Ω , " "	1-101-010-11	C ₃₁₆	2pF Ceramic
1-203-464-11	R ₉₁₃	560 K Ω , RD $\frac{1}{4}$ L, "	1-121-121-01	C ₃₁₇	200 μ F 12WV Electrolytic
1-201-455-00	R ₉₀₁	1.5 M Ω , RC $\frac{1}{2}$ L, Composition	1-101-048-11	C ₃₁₈	4pF Ceramic
1-201-455-00	R ₉₀₂	1.5 M Ω , " "	1-101-058-01	C ₃₁₉	5,000pF 50WV "
1-203-157-00	R ₉₀₃	680 Ω , RD $\frac{1}{4}$ L, Carbon	1-101-058-01	C ₃₂₀	5,000pF 50WV "
1-203-334-00	R ₉₀₄	180 Ω , " "		C ₃₂₁	—deleted—
1-203-129-00	R ₉₀₅	27 K Ω , " "	1-101-004-11	C ₃₂₂	0.001 μ F 50WV Ceramic
		Capacitor	1-103-096-11	C ₃₂₃	6pF Styrol
1-101-125-14	C ₁	1,000pF Ceramic	1-101-004-11	C ₃₂₄	0.01 μ F 50WV Ceramic
1-101-010-11	C ₂	2pF "	1-121-116-01	C ₃₂₅	1 μ F 12WV Electrolytic
1-101-076-11	C ₃	0.5pF "	1-127-911-11	C ₃₂₆	0.5 μ F 10WV " (Alox)
1-101-532-11	C ₄	15pF " (Disc)	1-101-004-11	C ₃₂₇	0.01 μ F 50WV Ceramic
1-101-531-11	C ₅	1,000pF "	1-121-122-01	C ₃₂₈	50 μ F 12WV Electrolytic
1-101-531-11	C ₆	1,000pF "	1-121-145-01	C ₃₂₉	1 μ F 5WV "
1-101-130-11	C ₇	12p "	1-101-004-11	C ₄₀₁	0.01 μ F 50WV Ceramic
1-101-002-12	C ₁₀₁	0.002 μ F 50WV "	1-101-010-11	C ₄₀₂	2pF "
1-101-562-11	C ₂₀₁	50pF "	1-101-113-18	C ₄₀₃	80pF "
1-141-060-11	C ₂₀₂	Cylindrical Trimmer Capacitor	1-101-004-11	C ₃₀₄	0.01 μ F 50WV "
1-101-575-11	C ₂₀₃	14pF Ceramic	1-101-012-11	C ₄₀₅	5pF "
1-101-561-11	C ₂₀₄	30pF "	1-101-115-17	C ₄₀₆	30pF "
1-101-565-11	C ₂₀₅	25pF "	1-101-007-11	C ₄₀₇	0.05 μ F 50WV "
1-101-568-11	C ₂₀₆	1pF "	1-101-740-17	C ₄₀₈	140pF " (Disc)
1-101-569-11	C ₂₀₇	12pF "	1-121-104-01	C ₄₀₉	10 μ F 6WV Electrolytic
1-141-060-11	C ₂₀₈	Cylindrical Trimmer Capacitor	1-121-104-01	C ₄₁₀	10 μ F 6WV "
1-101-072-14	C ₂₀₉	0.01 μ F Ceramic	1-121-102-01	C ₄₁₁	30 μ F 6WV "
1-101-125-11	C ₂₁₀	0.001 μ F "	1-121-120-01	C ₄₁₂	100 μ F 12WV "
1-141-060-11	C ₂₁₁	Cylindrical Trimmer Capacitor	1-121-135-01	C ₄₁₃	50 μ F 6WV "
1-101-556-11	C ₂₁₂	6pF Ceramic	1-121-121-01	C ₄₁₄	200 μ F 12WV "
1-101-559-11	C ₂₁₃	15pF "	1-121-122-01	C ₄₁₅	50 μ F 12WV "
1-101-561-11	C ₂₁₄	30pF "	1-101-004-11	C ₄₁₆	0.01 μ F 50WV "
1-101-559-11	C ₂₁₅	15pF "	1-101-007-11	C ₄₁₇	0.05 μ F 50WV "
1-101-573-11	C ₂₁₆	120pF "	1-121-118-01	C ₅₀₁	10 μ F 12WV Electrolytic
1-101-125-11	C ₂₁₇	0.001 μ F "	1-101-012-11	C ₅₀₂	5pF Ceramic
1-101-560-11	C ₂₁₈	20pF "	1-121-118-01	C ₅₀₃	10 μ F 12WV Electrolytic
1-101-553-11	C ₂₁₉	3pF "	1-101-113-12	C ₅₀₄	80pF Ceramic
	C ₂₂₀	Fine Tuning Capacitor	1-105-665-12	C ₅₀₅	0.0022 μ F 50WV Mylar
1-101-554-11	C ₂₂₁	4pF Ceramic	1-121-201-05	C ₅₀₆	100 μ F 15WV Electrolytic
1-101-572-11	C ₂₂₂	7pF "	1-105-889-12	C ₅₀₇	0.22 μ F 100WV Mylar
1-101-557-11	C ₂₂₃	10pF "	1-105-721-12	C ₅₀₈	0.047 μ F 100WV "
1-101-563-11	C ₂₂₄	50pF "	1-103-305-11	C ₅₀₉	500pF Styrol
1-101-125-11	C ₂₂₅	0.001 μ F "	1-105-673-12	C ₆₀₁	0.01 μ F 50WV Mylar
1-101-125-11	C ₂₂₆	0.001 μ F "	1-127-913-11	C ₆₀₂	2 μ F 10WV Electrolytic (Alox)
1-101-544-11	C ₂₂₇	1,800pF "	1-121-052-08	C ₆₀₃	10 μ F 10WV "
1-101-544-11	C ₂₂₈	1,800pF "	1-105-681-12	C ₆₀₄	0.047 μ F 50WV Mylar
1-101-544-11	C ₂₂₉	1,800pF "	1-105-669-12	C ₆₀₅	0.033 μ F 50WV "
1-101-560-11	C ₂₃₀	20pF "	1-105-673-12	C ₆₀₆	0.01 μ F 50WV Ceramic
1-101-555-11	C ₂₃₁	5pF "	1-127-906-00	C ₆₀₇	1 μ F 10WV Electrolytic
1-101-561-11	C ₂₃₂	30pF "	1-105-685-12	C ₆₀₈	0.1 μ F 50WV Mylar
1-101-086-01	C ₂₅₁	0.1 μ F 50WV "	1-105-683-12	C ₆₀₉	0.068 μ F 50WV "
1-101-086-01	C ₂₅₂	0.1 μ F 50WV "	1-127-908-00	C ₆₁₀	3 μ F 10WV Electrolytic (Alox)
1-101-001-11	C ₃₀₁	0.001 μ F 50WV "	1-121-051-08	C ₆₁₁	100 μ F 6WV "
1-101-010-11	C ₃₀₂	2pF "	1-121-021-11	C ₇₀₁	1,000 μ F 12WV "
1-101-004-11	C ₃₀₃	0.01 μ F 50WV "	1-121-119-01	C ₇₀₂	30 μ F 12WV "
1-101-111-18	C ₃₀₄	20pF "	1-131-008-11	C ₇₀₃	30 μ F 10WV " (Tantalum)
1-101-010-11	C ₃₀₅	2pF "	1-121-188-05	C ₇₀₄	50 μ F 12WV "
1-101-011-11	C ₃₀₆	3pF "	1-127-921-11	C ₇₀₅	5 μ F 10WV " (Alox)
1-101-114-17	C ₃₀₇	15pF "	1-121-127-01	C ₇₀₆	20 μ F 10WV "
1-101-010-11	C ₃₀₈	2pF "	1-121-122-01	C ₇₀₇	50 μ F 12WV "
1-101-004-11	C ₃₀₉	0.01 μ F 50WV "	1-121-120-01	C ₇₀₈	100 μ F 12WV "
1-101-004-11	C ₃₁₀	0.01 μ F 50WV "	1-121-142-01	C ₇₀₉	5 μ F 50WV "

Part No.	Symbol	Description	Part No.	Symbol	Description
1-105-721-12	C ₇₁₀	0.047 μ F 100WV Mylar	1-101-539-11	C ₈₁₂	500pF 7.5 KV Ceramic
1-105-721-11	C ₇₁₁	0.047 μ F " "	1-101-539-11	C ₈₁₃	500pF 7.5 KV "
1-105-677-12	C ₈₀₁	0.022 μ F 50WV "	1-101-539-11	C ₈₁₄	500pF 7.5 KV "
1-105-681-12	C ₈₀₂	0.047 μ F " "	1-105-278-11	C ₈₁₅	7 μ F 50WV Mylar (Metalized)
1-105-669-12	C ₈₀₃	0.033 μ F " "	1-113-122-11	C ₈₁₆	0.05 μ F 500WV PS Capacitor
1-105-681-12	C ₈₀₄	0.047 μ F " "	1-105-097-00	C ₈₁₇	0.3 μ F 35WV Mylar
	C ₈₀₅	—deleted—	1-105-167-11	C ₈₁₈	0.01 μ F 200WV "
1-121-197-01	C ₈₀₆	500 μ F 15WV Electrolytic	1-109-010-11	C ₉₀₁	200pF Mica
1-105-274-11	C ₈₀₇	0.01 μ F + 0.005 μ F 200WV Mylar (Block)	1-109-010-11	C ₉₀₂	200pF "
			1-119-071-01	C ₉₀₃	4,000 μ F 15WV Electrolytic
1-105-273-11	C ₈₀₈	0.09 μ F 250WV "	1-119-071-01	C ₉₀₄	4,000 μ F 15WV "
1-105-721-12	C ₈₀₉	0.047 μ F " "	1-119-106-11	C ₉₀₅	100 μ F 15WV "
1-121-126-00	C ₈₁₀	10 μ F 100WV Electrolytic	1-119-042-01	C ₉₀₆	50 μ F 12WV "
1-113-122-11	C ₈₁₁	0.05 μ F 500WV PS Capacitor	1-119-044-01	C ₉₀₇	30 μ F 12WV "

Electrical Parts List (B)

Part No.	Description	Q'ty	Part No.	Description	Q'ty
A. General			B. Wire & Miscellaneous		
Cabinet & Appearance Items			(Minimum q'ty for ordering: Meter)		
1-507-030-10	Earphone Jack	1	Main Block		
1-514-107-11	Battery Charger Switch	1	P. V. C. Wire		mm
1-502-089-11	Speaker	1	26/0.16	Brown	1380
4-003-301-01	Speaker Grommet	4	"	Black	275
X-40032-84-2	Antenna Jack Ass'y	1	"	Red	230
Main Block			16/0.16	Black	935
1-526-052-04	Picture Tube Socket	1	"	White	985
1-545-002-11	Multi-Jack	2	"	Purple	40
1-533-016-11	Fuse Holder	1	"	Gray	265
1-506-050-11	4 P Plug	1	"	Green	205
1-536-052-11	Terminal Strip	1	"	Orange	460
1-532-035-11	Fuse (2A)	1	"	Brown	225
1-519-007-15	Neon Lamp	1	"	Yellow	540
1-536-054-11	Terminal Strip 1-1P	1	"	Blue	270
Accessory			26/0.16	Blue	100
X-40032-32-1	Accessory Ass'y, including	1	Two Conductor Microphone Cord		
1-534-041-20	AC Cord	(1)	7/0.12		35
1-534-042-21	Extension Cord	(1)	Tinned Copper Wire		
1-504-010-02	Earphone	(1)	0.6 ϕ		205
X-44017-31-1	External Antenna Connector EAC-6	1	Video & Sound Signal Block		
Deflection Block			P. V. C. Wire		
1-538-137-12	Deflection Circuit Board	1	16/0.16	Black	612
1-506-103-00	Connecting Pin	9	Deflection Block		
1-507-109-00	Connector Tip	1	P. V. C. Wire		
Video & Sound Signal Block			16/0.16	Black	470
1-538-136-12	Video & Sound Signal Circuit Board	1	"	Yellow	130
1-506-108-00	Connecting Pin	3	Tinned Copper Wire		
1-507-109-00	Connector Tip	1	0.6 ϕ		15
			High Voltage Block		
			Polyethylene Wire 4.2 ϕ		20
			Advance Wire		425
			Deflection Yoke		
			P. V. C. Wire		
			26/0.16	Brown	12
			"	Red	12
			10/0.16	Green	17
			"	Gray	17

Part No.	Description	Q'ty	Part No.	Description	Q'ty
BT-501	Tuner Block (including UHF and VHF)	1	1-453-002-12	High Voltage Block	1
X-40032-52-1	Video & Sound Signal Block (Mounted)	1	1-451-005-13	Deflection Yoke	1
-53-1	Deflection Block (Mounted)	1			

Mechanical Parts List

Part No.	Description	Q'ty	Part No.	Description	Q'ty
A. General			4-003-348-01	Front Cover Badge (UW)	(1)
Cabinet & Appearance Items			4-003-239-01	Adjustment Hole Cover	1
X-40032-02-2	Picture Tube Mask Assembly, including	1	-240-01	Bottom Cover	1
4-003-204-02	Picture Tube Mask	(1)	-241-01	Circuit Board Holding Bracket	1
-205-01	" SONY " Badge	(1)	X-40032-08-3	Table Stand Assembly, including	2
-206-01	Picture Tube Fixing Bracket (left)	(2)	4-003-242-03	Table Stand	(2)
-207-01	" (right)	(2)	-243-02	Reinforcing Plate for Table Stand	(2)
X-40032-03-1	Control Panel Assembly, including	1	X-40032-09-1	Back Cover (UW) Assembly, including	1
4-003-203-01	Control Panel Mounter	(1)	4-003-244-03	Back Cover	(1)
-209-01	Control Panel	(1)	-245-02	Name Plate (UW)	(1)
-210-01	Dial Ring (inside)	(1)	4-002-816-01	Badge No. Label	1/10
-211-01	Dial Ring	(1)	X-40032-10-2	Channel Selector Knob (UW) Assembly, including	1
-212-01	Dial Cover	(1)	4-003-246-01	Channel Selector Knob (UW)	(1)
-213-01	Control Panel Mounter Holding Bracket	(2)	-247-01	Channel Selector Indicating Plate (UW)	(1)
4-003-214-01	Picture Tube Protector	1	-248-01	Channel Selector Knob Spring (UW)	(1)
-215-02	Dust-proof Rubber	1	-023-01	Channel Selector Knob Cushion	(1)
-216-02	Picture Tube Holding Ring	1	X-40032-12-1	Fine Tuning Knob (UW) Assembly, including	1
X-40032-04-1	Picture Tube Holding Bracket Assembly, including	4	4-003-249-02	Fine Tuning Knob (UW)	(1)
4-003-217-01	Picture Tube Holding Bracket	(4)	-250-01	Fine Tuning Knob Spring	(1)
-218-01	Cushion for Picture Tube Holding Bracket	(4)	X-40032-13-1	Control Knob Assembly, including	4
4-003-219-01	Cushion for Picture Tube	1	4-003-251-01	Control Knob	(4)
-220-02	Grounding Spring	1	-252-01	Control Knob Spring	(4)
X-40032-05-1	Cabinet Assembly	1	X-40032-14-1	Volume Control Knob Assembly, including	1
X-40032-06-3	Grip Handle Assembly, including	1	4-003-253-01	Volume Control Knob	(1)
4-003-223-02	Grip Handle	(1)	-254-01	Volume Control Knob Panel	(1)
-224-02	Ornamental Leather for Grip Handle	(1)	-252-01	Volume Control Knob Spring	(1)
-227-03	Felt for Grip Handle	(2)	4-003-345-01	Packing for Volume Control Knob	5
4-003-233-01	Grip Handle Receptacle	2	Main Block		
-225-01	Grip Handle Bearing (left)	1	X-40032-15-1	Chassis Assembly, including	1
-226-01	" (right)	1	4-003-256-01	Chassis	(1)
-228-01	Speaker Grille	4	-257-01	Adjustable Clamp for Electrolytic Capacitor (large)	(1)
-329-02	Speaker Holding Nut	4	4-003-259-01	Multi-Jack Holding Bracket	1
X-40032-83-2	Telescopic Antenna Assembly, including	1	-260-02	Adjustable Clamp for Electrolytic Capacitor (small)	1
X-40026-71-1	Telescopic Antenna Sub-Assembly	(1)	-261-01	Volume Control Holding Plate	1
4-002-840-01	Telescopic Antenna Ball	(1)	-292-01	Tuner Holding Bracket	1
-841-01	Telescopic Antenna Ball Receptacle	(1)	-293-01	Pilot Lamp Holder	1
-842-01	Telescopic Antenna Spring	(1)	Video & Sound Signal Block		
-843-01	Special Washer	(2)	4-003-330-02	Shielded Plate for Video & Sound Signal Circuit Board	1
-844-01	Telescopic Antenna Supporter	(1)	-344-02	Rubber Bushing for Video & Sound Signal Circuit Board	2
-845-01	Telescopic Antenna Fixing Shaft	(1)	Deflection Block		
-717-00	Telescopic Antenna Bottom Insulator	(1)	X-40032-01-1	Deflection Circuit Board Assembly (not printed), including	1
4-003-343-02	Telescopic Antenna Holding Plate	(1)	4-003-201-01	Heat Sink for Hor. Power Transistor	(1)
-232-03	Telescopic Antenna Washer	(1)	-202-01	Heat Sink for Vert. Power Transistor	(1)
-334-01	Telescopic Antenna Lug	(1)	-203-01	Spacer for Heat Sink	(1)
7-623-112-11	Washer 5 ϕ (medium)	(1)	4-002-107-01	Heat Sink for Hor. Driver Transistor	(1)
-412-02	Star Washer 5 ϕ	(1)	Accessory		
4-002-727-00	Telescopic Antenna Holding Nut 5 ϕ	(1)	4-003-277-01	Styro-Foam Cushion (left)	1
-728-00	Lock Nut for Telescopic Antenna 5 ϕ	(1)	-278-01	" (right)	1
-764-01	Antenna Tip	(1)	-358-01	Master Carton (for 2 sets)	1/2
4-003-342-01	Telescopic Antenna Bushing	1			
-346-01	Telescopic Antenna Clamper	1			
X-40032-98-1	Front Cover (UW) Assembly, including	1			
4-003-347-01	Front Cover	(1)			

Part No.	Description	Q'ty	Part No.	Description	Q'ty
4-003-279-01	Carton for Cabinet	1		Nut	
4-002-770-00	Polyethylene Bag	1	7-622-207-01	2.6φ (for Telescopic Antenna Clamper)	1
4-495-025-11	Instruction Manual	1	-208-01	3φ (for Picture Tube (2), Table Stand (2))	4
X-44900-02-1	Silicone Cloth (in Polyethylene Bag)	1	4-003-355-01	6φ (for Grip Handle)	2
4-490-012-00	Polyethylene Bag	(1)		Main Block	
3-998-911-01	Silicone Cloth	(1)		Screw	
X-40032-96-1	Caution Tag Assembly, including	1	7-621-261-02	⊕P 3φ × 6 (for Tuner (2), Charger Switch (2), Volume Control (4), Multi-Jack (2), High Voltage Block (2), 4 P Plug (2), Fuse Holder (1), Adjustable Clamp (1), Power Transformer (2), Electrolytic Capacitor (1))	17
4-003-408-01	Caution Card	(1)	-52	⊕P 3φ × 8 (for Video & Sound Signal Circuit Board)	2
4-498-002-10	Adjust Card	(1)	-62	⊕P 3φ × 10 (for Electrolytic Capacitor)	1
4-003-284-01	Inspection Card	(1)	4-002-737-01	⊕P 3φ × 23 (for Selenium Rectifier)	1
	B. Screw & Washer			Spring Washer	
	(Minimum q'ty for ordering: 100pcs.)		7-623-208-21	3φ (for Tuner (2), Volume Control (2), High Voltage Block (2), Adjustable Clamp (1), Power Transformer (1), Charger Switch (2), Multi-Jack (1))	8
	Cabinet & Appearance Items			Star Washer	
	Screw		7-623-408-01	3φ (for Selenium Rectifier)	1
7-621-559-69	⊕K 2.6φ × 10 (for Telescopic Antenna Clamper)	1		Washer	
-770-39	⊕B 3φ × 8 (for Picture Tube Mask (4), Control Panel Mounter (2))	6	7-623-108-12	3φ (for Video & Sound Signal Circuit Board)	2
-261-52	⊕P 3φ × 8 (for Chassis)	2		Video, Sound Signal Block and Deflection Block	
-770-40	⊕B 3φ × 10 (for Speaker)	4		Screw	
-261-42	⊕P 3φ × 6 (for Deflection Circuit Board (1), Picture Tube (4), Table Stand (2), Telescopic Antenna (2))	9	7-621-261-62	⊕P 3φ × 10 (for Transistor 2SC41)	4
-770-26	⊕B 2.6φ × 6 (for External Antenna Jack)	1	-72	⊕P 3φ × 12 (for Transistor 2SB232)	2
-263-02	⊕P 3φ × 50 (for Picture Tube)	1	-255-52	⊕P 2φ × 8 (for Transistor 2SC140)	2
	Self Tapping Screw			Star Washer	
7-621-722-51	⊕R 3φ × 8 (for Chassis (2), Circuit Board Holding Bracket (1), Deflection Circuit Board (2), Bottom Cover (4))	9	7-623-408-01	3φ (for Transistor 2SC41 (4), 2SB232 (2))	6
-61	⊕R 3φ × 10 (for Table Stand)	4	-405-01	2φ (for Transistor 2SC140)	2
-71	⊕R 3φ × 12 (for Bottom Cover)	5		Nut	
	Star Washer		7-622-308-01	3φ (for Transistor 2SB232 (2), 2SC41 (4))	6
7-623-407-01	2.6φ (for Telescopic Antenna Clamper)	1	-305-01	2φ (for Transistor 2SC140)	2
-413-01	6φ (for Grip Handle)	2			
	Washer				
7-623-108-11	3φ (medium) (for Back Cover (5), Picture Tube (1))	6			
	Spring Washer				
7-623-208-21	3φ (for Picture Tube)	4			

SONY CORPORATION